COMPDYN 2009

ECCOMAS Thematic Conference on Computational Methods in Structural Dynamics and Earthquake Engineering M. Papadrakakis, N.D. Lagaros, M. Fragiadakis (eds.) Rhodes, Greece, 22–24 June 2009

## R&D ON CONTROL OF VIBRATIONS UNDER COVICOCEPAD DURING 2007-2008

R.C. Barros<sup>1</sup>, A. Baratta<sup>2</sup>, O. Corbi<sup>2</sup>, M.B. César<sup>1</sup>, I. Corbi<sup>2</sup> R. Bairrão<sup>3</sup>, L. Guerreiro<sup>4</sup>, C. Oliveira<sup>4</sup>, G. Magonette<sup>5</sup>

<sup>1</sup> FEUP – Faculdade de Engenharia, Universidade do Porto (UP), Portugal Department of Civil Engineering, Rua Roberto Frias, 4200-465 Porto, Portugal e-mail: <a href="mailto:rcb@fe.up.pt">rcb@fe.up.pt</a>, <a href="mailto:dec05002@fe.up.pt">dec05002@fe.up.pt</a>

<sup>2</sup> University of Naples Federico II, Naples, Italy Department of Structural Engineering, via Claudio 21, 80125 Napoli, Italy Alessandro.baratta@unina.it, ottavia.corbi@unina.it, Ileana.corbi@unina.it

<sup>3</sup> LNEC – National Laboratory of Civil Engineering Avenida do Brasil, Lisboa, Portugal bairrao@lnec.pt

<sup>4</sup> IST – Instituto Superior Técnico, Universidade Técnica de Lisboa (UTL), Portugal Dept Civil Engng, Avenida Rovisco Pais, Lisboa, Portugal luisg@civil.ist.utl.pt

<sup>5</sup> Structural Mechanics Laboratory, ELSA Unit Institute for the Protection and Security of the Citizen (IPSC) Joint Research Centre, 21020 Ispra, Italy georges.magonette@jrc.it

**Keywords:** Control of Vibrations for Smart Structures, Semi-Active Devices, MR Dampers, TLD and Base Isolation devices, Experimental Tests on Shaking Table.

**Abstract.** This paper provides information on the latest R&D within COVICOCEPAD project approved in the framework of Eurocores program. It addresses the use of TLD, base isolation devices, MR dampers and a hybrid technique using both devices together. Some results are provided associated with calibration of a MR damper at FEUP, as well as its inclusion in a small scale laboratory set-up with proper equations of motion of the controlled smart structure. An application of semi-active control technique to a bridge is outlined. Further remarks and details on future tests to be performed in LNEC shaking table, within COVICOCEPAD project, are provided.